HSRM11010

ABUS Smoke Detector, Lithium, set of 3

The set provides you with three smoke detectors HSRM11010 at a preferential price.
The photoelectrical ABUS smoke detector reacts to smoke particles. If too much smoke enters its measuring chamber, a loud alarm signal is triggered. The smoke detector is mounted at the ceiling in the center of a room. The minimum distance to the walls should be 15 cm, the distance to the corners at least 50 cm. The operation range of the smoke detector is up to 40 m². We recommend installing each one smoke detector in the hall, the stairways, living room and bedroom. In the event of fire, the integrated powerful piezo sounder provides an effective alarming – at a minimum sound level of 85 dB.
When using a corresponding battery (9 V Lithium), the lifetime is up to 10 years. The battery lifetime varies depending on how often you run the detector's function test. This is done easily by pressing the function test button; recommended: test once a week. A low battery is notified by the detector, issuing regular beep tones. The home smoke detector is VdS approved. This guarantees high safety.

© 2012 ABUS Security–Center GmbH & Co. KG, Errors and omissions excepted.

HSRM11010

ABUS Smoke Detector, Lithium, set of 3

Technical Data	
Display	LED
Detector type	Photoelectrical reflection
Detection range	40 m²
Sensor type	Photo diode
Certificates	VdS
Power supply	9 V Lithium battery
Battery type	Block battery
Battery lifetime	up to 10 years
Housing material	ABS
Area of installation	Ceiling
Operation temperature	0°C to +45°C
Dimensions (HxD)	Dimensions (HxD)
Weight	180 g

© 2012 ABUS Security–Center GmbH & Co. KG, Errors and omissions excepted.